

IQ, MIXER

2.0 to 4.0 GHz

IQ2040MF4

PRODUCT FEATURE

- †Broadband Frequency Application
- †Excellent Conversion Loss
- †High Isolation
- †Frequency Converter Application

ABSOLUTE MAXIMUM RATING:

Operating Temperature:	-54°C to +125°C
Storage Temperature:	-65°C to +150°C
Peak Input Power for any Single Port:	+23 dBm Peak
Peak Input Power for all Port:	+26 dBm Peak
Peak Input Current @ 25°C:	100 mA

Parameters	SPECIFICATION @ 25°C				
	FREQ. (GHz)	MIN (dB)	TYPICAL (dB)	MAX (dB)	CONDITONS
CONVERSION LOSS					
RF INPUT	2.0 to 4.0		5.5	7.0	IF=100MHz
LO INPUT	2.0 to 4.0				
IF OUTPUT	DC to 0.5				
VSWR	LO & IF RF		2.5		
ISOLATION					
LO-RF		30	40		
LO-I/Q		25	30		
RF-I/Q			30		
1 dB Compression Point			+1dBm		
LO Drive			+10dBm		
IMAGE REJECTION		19 dB	28 dB		
AMPLITUDE MATCH			0.2 dB		
PHASE MATCH			2.0°		

NOTES:

1. Typical values are measured at +25°C and are not guaranteed

IQ, MIXER

2.0 to 4.0 GHz

IQ2040MF4

