

IR, MIXER

4.1 to 6.1 GHz

IR3060MF2-125

PRODUCT FEATURE

- †Broadband Frequency Application
- †Excellent Conversion Loss
- †High Isolation
- †Frequency Converter Application

ABSOLUTE MAXIMUM RATING:

Operating Temperature:	-54°C to +125°C
Storage Temperature:	-65°C to +150°C
Peak Input Power for any Single Port:	+23 dBm Peak
Peak Input Power for all Port:	+26 dBm Peak
Peak Input Current @ 25°C:	100 mA

Parameters	SPECIFICATION @ 25°C				
	FREQ. (GHz)	MIN (dB)	TYPICAL (dB)	MAX (dB)	CONDITONS
CONVERSION LOSS					
RF OUTPUT	3.2 to 5.2		7.0	8.0	
LO INPUT	4.1 to 6.1				
IF INPUT	0.9				
VSWR	LO & IF RF		2.0		
ISOLATION					
LO-RF		25	30		
LO-IF		25	28		
SPURS, IN BAND, (4IF)			-60 dBC		
1 dB Compression Point			+4dBm		
LO Drive			+10 dBm	+14 dBm	
IMAGE REJECTION		16 dB	18 dB		
OPERATING TEMP RANGE(°C)		-40		+85	

NOTES:

1. Typical values are measured at +25°C and are not guaranteed

IR, MIXER

4.1 to 6.1 GHz

IR3060MF2-125

