

Ultra-Broadband Directional Coupler


1.7 to 26.5 GHz

MODEL NO: ECP226516

- **Low Loss**
- **Excellent Frequency Sensitivity**
- **Power: 20WCW/3KW Peak**

Parameters	SPECIFICATION				Units
	FREQ. (MHz)	MIN	TYPICAL	MAX	
Insertion Loss	1700 to 26500		1.2	1.3	dB
VSWR	1700 to 26500		1.50:1	1.55:1	
Directivity	1700 to 26500	+14	+16		dB
Coupling (1)	1700 to 26500		16		dBm
Frequency Sensitivity(1)	1700 to 26500		± 0.45	± 0.55	dB
CW Power Handling				20	Watt
Power Handling (Peak) (1 usec Pulse Width, 0.1% Duty Cycle)				3000	Watts

1. Reference to output power



Dimensions - inches [mm]								
Outline	A	B	C	D	E	F	G	H
1	3.5 [88.90]	0.73 [18.54]	N/A	N/A	N/A	1.0 [25.4]	1.25 [31.75]	0.25 [6.35]
2	2.4 [60.96]	0.69 [17.52]	0.38 [9.65]	0.66 [16.76]	1.078 [27.38]	0.75 [19.05]	0.80 [20.32]	0.31 [7.87]